



SINAK *Finishing Aid*

PRODUCT DESCRIPTION

SINAK Finishing Aid is a universal proprietary formulated, water based material designed to reduce friction while troweling freshly placed concrete. **SINAK Finishing Aid** is compatible with all known curing compounds, curing aids, and evaporation retarders.

SINAK Corporation recognizes that each concrete placement is unique. Weather conditions, mix designs and geography all play a role in the ability to finish the concrete surface. To determine the need for use and coverage rates, a small test sample is recommended.

ADVANTAGES

- **Universally compatible**
- **Increased workability**
- **Reduces dusting**
- **Mitigates plastic shrinkage cracks**
- **Unlimited shelf life**

TECHNICAL INFORMATION

Composition and Materials:

SINAK Finishing Aid is a water-based liquid with a proprietary formula in solution. It requires NO mixing, diluting or agitation. Color: Water clear; Specific Gravity: 1.03; Net Weight: 8.6 lbs/gal; Flash Point: none; Toxicity: Non-toxic; VOC: Contains NO volatile organic compounds or solvents.

INSTALLATION

General Application Instructions:

SINAK Finishing Aid is a ready to use formula. May be used in ride on power trowels, 3 gal pump sprayers or small spray bottles for use on hand tools. SINAK Corporation recommends that a 0.50 GPM fan spray tip or smaller be used.

Approximate Coverage Rates (Subject to surface finish):

SINAK Finishing Aid is a ready to use formula designed for an application rate of 600 sq ft or greater. Contact SINAK Corporation for additional information.

Storage and Handling:

SINAK Finishing Aid has an indefinite shelf life when stored in a cool dry area out of direct sunlight. Must be kept in tightly secured containers to prevent evaporation and contamination. **SINAK Finishing Aid** MUST be protected from freezing. Product that has frozen will not function as intended and should be discarded.

Precautions:

Apply only enough material as needed based on the site testing. Do not flood the surface. Do not allow to puddle. Protect adjoining surfaces from overspray. Flush spray equipment and tools with warm soapy water.

AVAILABILITY

SINAK Finishing Aid is available in 5-gallon pails, 55-gallon drums and 275-gallon totes from selected distributors.

MAINTENANCE

After application, no special maintenance is required.

TECHNICAL ASSISTANCE

Technical assistance is available from the manufacturer and trained field representatives.

SINAK SYSTEMS

- **SINAK Finishing Aid:** used on all concrete, grout and mortar products.
- **SINAK VC-5:** Moisture vapor and alkalinity control curing agent with 15yr flooring warranty.
- **SINAK LithiumCure 2000:** for Hard trowelled/burnished slabs or polished concrete.
- **SINAK LithiumCure 1000:** for all exterior open surface profiled concrete.
- **SINAK WCE:** Potable water applications.

LIMITED WARRANTY

SINAK Corporation warrants its products to be of the highest quality. Since application of the product is a crucial factor in obtaining satisfactory results, and is beyond the control of SINAK Corporation, refund of purchase price or replacement of product shall constitute the limit of SINAK Corporation's liability. SINAK Corporation makes no other warranties, express or implied, with respect to the products or any service and disclaims all other warranties, including any warranty of merchantability and fitness for a particular purpose. This limited warranty may not be modified by representatives of SINAK Corporation, its distributors or dealers.

