

SINAK CORPORATION

Warranty

This WARRANTY presented to:

Name: _____

Address: _____

For: Project: _____

Address: _____

Application date: _____ Area treated: _____ sq ft

SINAK Corporation warrants that VC5 is of the highest quality as measured by exacting manufacturing standards. When applied in full accordance with written application instructions, VC5 will prevent flooring failure due to moisture, moisture vapor, and alkalinity emanating from the concrete for a minimum period of 15 years from the date of application. This warranty will remain in effect should the surface be damaged during the construction phase; or should mechanical preparation be done prior to the installation of flooring or coatings. This warranty is non-prorated and transferable should the property be sold or transferred during the warranty period. Bond of adhesives is also warranted when applied in strict accordance with manufacturer's written instructions and is used prior to the expiration date. Note: Glue down wood floors require an application of SINAK V-Poxy prior to installation. For further information contact SINAK Corporation.

Conditions and Exclusions

Concrete treated with VC5 must have a water/cement ratio of 0.50 or less, and must have been mixed, placed, and finished in accordance with guidelines by the ACI (American Concrete Institute) Manual of Standard Practice, section 302. This warranty does not cover failures from causes other than moisture, moisture vapor, or alkalinity emanating from the concrete causing adhesives or coatings to fail due to high concentration of alkaline salts originating from the concrete.

Concrete containing any of the following is not covered by this warranty: aggregate considered deleterious as noted in ASTM C33/C33M-16, section 7.3; and "Causes of Floor and Slab Imperfections" in the ACI Manual of Standard Practice, section 302, Chapter 5 part 5.7. Admixtures containing chloride, silicate or water repellants are not covered under this warranty. Chemicals and contaminants introduced by the underlying soil are not covered under this warranty. Topical intrusion of moisture or chemicals is not covered under this warranty. Improper installation including, but not limited to, failure to comply with SINAK's product coverage rate as described in its instructions, use or defects associated with preparation materials, adhesives, flooring goods or coatings are not covered under this warranty. Damage caused by movement of joints and cracks is not covered under this warranty.

Remedy

In the event of failure of floor covering materials from moisture, moisture vapor, or alkalinity emanating from the concrete; and, subject to and without limitation, the above Conditions and Exclusions, SINAK Corporation will provide materials and labor to retreat and/or recoat the affected area(s); including replacement of floor covering in the affected area(s). Retreated/recoated area(s) shall be covered for the remainder of the warranty period. **This is our only warranty. We make no other warranty, express or implied, including merchantability or fitness for a particular purpose.**

Manufacturer:

SINAK Corporation
4901 Morena Blvd, Ste 601
San Diego, CA 92117

By: _____

Title: _____

(WARRANTY not valid without signature and seal of SINAK Corporation)